



PROPOSED GROUND FLOOR LAYOUT

REV. NO.	DESCRIPTION	REV. BY	DATE	CLIENT	SHEET TITLE	HOSPITAL PLANNERS
				MGM HOSPITAL & RESEARCH CENTRE	GROUND FLOOR (FOR AERB SUBMISSION)	HOSMAC PERFECTING HEALTHCARE
				Design & Project Advisory Services at MGM Hospital, Sanpada.	DRAWING NO.	LMT-02 LLOYD BHAVAN, SONAPADA ROAD, GOREGAON (WEST), MUMBAI-400 043 TEL: +91-22-2552-2888 FAX: +91-22-2552-2888 DRAWING DETAILS:
GENERAL NOTES: 1) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 2) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 3) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 4) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 5) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 6) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 7) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 8) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 9) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED. 10) ALL DIMENSIONS AND ACCOMPANYING SPECIFICATIONS ARE IN METERS UNLESS OTHERWISE STATED.				NOTE & LEGEND: 1) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 2) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 3) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 4) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 5) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 6) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 7) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 8) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 9) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK. 10) UNLESS NOTED OTHERWISE (IN CO.) ALL EXTERNAL WALLS SHALL BE 200MM THICK AND ALL INTERNAL WALLS SHALL BE 100MM THICK.		DRAWN BY: RR CHECKED BY: AG PROJECT NO: HP-412 SCALE: 1:125 DRAWING STATUS: FOR APPROVAL DATE: 06/07/2022

REVISED: R0